
# La linea - 2,5mt

## BIG - Bjarke Ingels Group



IP65 ( C € Dimmerable: +0-



#### LUMINAIRE

- Watt: 15W/m

- Delivered lumens output: 960 lm/m

CCT: 3000KEfficiency: 100%Efficacy: 64lm/W

- CRI: 95

- Dimmable Typology: APP, Push, Dali

#### Notes

5 wall/ceiling supports included

#### **DESCRIPTION**

La Linea is a basic principle that generates an open system and a comprehensive relation with space and humans. It turns light into an ideal fixture for outdoor spaces, architectures, parks, or public and urban areas to requalify common spaces, create social and engaging landscapes and promote relations between people and their surroundings.

It easily fits into indoor and outdoor spaces by leveraging on an unprecedented combination of factors, including quality of light, IP protection grade, flexibility, modularity.

BIG's idea is once again transposed, thanks to the know-how of Artemide, into a product that looks basic but it is rich of technological innovation.

Today, new installation possibilities make it an increasingly transversal solution. With an aluminum back bone is possible to suspend La Linea modules creating linear or curved geometries in custom composition.

With the new recessed accessories La Linea can be suspended from the extremities and can freely define the softly curving geometries during installation in the space.

#### PRODUCT CODE: T4601010

#### **FEATURES**

- Article Code: **T4601010** 

- Colour: White

- Installation: CeilingWall

- Material: Silicone flexible tube

Series: Design Collection, 2021 Artemide

**Collection, Architectural Outdoor** 

- Environment: Indoor

- design by: BIG - Bjarke Ingels Group

#### **DIMENSIONS**

Length: cm 250Diameter: cm 4



### Accessories

NO IMAGE AVAILABLE	Additional wall/ceiling support R304975	no image available	Driver 120W - CV 220-240V - 24VDC - SELV - Undimmable - IP20 DV1033
NO IMAGE AVAILABLE	Driver 90W - CV 100-240VAC - 24VDC - 0-10V - IP65 DV1075	NO IMAGE AVAILABLE	Driver 90W - CV 110-240VAC - 24VDC - APP+PUSH dim - IP20 DV1075APP
NO IMAGE AVAILABLE	Driver 90W - CV 100-240VAC - 24VDC - DALI dim - IP65 DV1076	no Image available	Powerkit 96W - CV 110-240VAC - 24VDC - Non Dimmerabile - IP65 A4681210
NO IMAGE AVAILABLE	Powerkit 96W - CV 110-240VAC - 24VDC - DALI/0- 10V/PUSH - IP20 A4681010	NO IMAGE AVAILABLE	Powerkit 96W - CV 110-240VAC - 24VDC - APP+PUSH - IP20 A4681010APP
NO IMAGE AVAILABLE	Powerkit 96W - CV 110-240VAC - 24VDC - APP+PUSH - IP65 T4681010APP		

